



CSLF-T-2005-3
Draft

DRAFT

Discussion Paper from the Task Force for Identifying Gaps in CO₂ Monitoring and Verification of Storage

Barbara N. McKee
Tel: 1 301 903 3820
Fax: 1 301 903 1591
CSLFSecretariat@hq.doe.gov



CSLF-T-2005-3
Draft

Discussion Paper from the Task Force for Identifying Gaps in CO₂ Monitoring and Verification of Storage

Note by the Secretariat

Background

At the meeting of the Technical Group in Melbourne, Australia on September 15, 2004, a Task Force was created to identify gaps in CO₂ monitoring and verification of storage. This Task Force consists of Canada (lead), the European Commission, France, Norway, and the United Kingdom. It was instructed to produce a Discussion Paper that would then undergo review and be presented at a full Technical Group meeting. This draft Discussion Paper is the result of the Task Force's activities.

Action Requested

The Technical Group is requested to review and consider the Discussion Paper presented by the Task Force for Identifying Gaps in CO₂ Monitoring and Verification of Storage.

Conclusions

The Technical Group is invited to note in the Minutes of its meeting of April 30, 2005 that:

“The Technical Group reviewed and considered the Discussion Paper presented by the Task Force for Identifying Gaps in CO₂ Monitoring and Verification of Storage.”

Discussion Paper: Identifying Gaps in CO₂ Monitoring and Verification of Storage

**Developed by a Task Force under the Technical Group
of the Carbon Sequestration Leadership Forum (CSLF)**

Task Force Members:

Bill Reynen and Malcolm Wilson, Canada
Nick Riley, European Commission
Taoufik Manai, France
Odd Magne Mathiassen, Norway
Sam Holloway, United Kingdom

Abstract:

Monitoring of CO₂ injection for enhanced oil recovery as well as the monitoring of a variety of other underground fluid storage operations has been ongoing for some decades. Regulations are in place in various, but certainly not all, countries of the world for enhanced oil recovery projects requiring solvent injection (CO₂, hydrocarbons), injection and storage of natural gas, injection of acid gas (a mixture of CO₂ and H₂S) and the injection of oilfield waste. The regulations include the standards for completion of injection wells, the maximum injection pressures allowed to avoid reservoir fracture, maximum allowable injection rates, expected storage performance before injection permits are offered and the regulations surrounding abandonment.

Future volumes of CO₂ injected underground will increase significantly over present and historic levels if fossil fuel use is going to continue to increase in a carbon- constrained world. The injection of CO₂ will differ from the injection of oil field waste fluids since the two are different in the sense that CO₂ is a buoyant fluid. CO₂ dissolved in water is also an acid and, therefore, reactive. In the longer term, the solubility and reactivity of the CO₂ will increase the permanence of the storage. Provided the storage is undertaken in suitable geological environments, the most likely pathway for leakage will be the engineered infrastructure (the wellbores or other human intrusions). There will need to be modification of, or addition to, current regulations to ensure human and ecosystem health and safety and to prevent the CO₂ from entering the atmosphere. These regulations will require monitoring regimes to ensure that the performance of the injection site meets the predicted performance for licensing.

This paper examines the current monitoring techniques in use in underground fluid injection and storage operations and evaluates the value of these techniques for storage monitoring, regulatory requirements and safety issues. Where gaps exist, for reasons of cost, resolution or other factors, these gaps are identified. Finally, recommendations are made for ongoing work to improve the cost, resolution and reliability of the techniques. Ultimately, it will be the regulator, assessing the risk of given sites, that will determine the nature of the monitoring to be undertaken and the length of time over which monitoring must occur. The recommendations in this paper do not call for technologies to be dropped from the slate of technologies we have available, rather the need for more work in

many areas in parallel to other processes to ensure that appropriate monitoring technologies are available to meet most monitoring requirements. The expectation is that different sites may well require different monitoring regimes.

Introduction:

The purpose of this paper is to provide commentary on the currently available technology for the monitoring and verification of carbon dioxide stored in the subsurface and to identify gaps or weaknesses in the available technologies. Based on this gap analysis, needs have been identified and recommendations for meeting the identified needs are proposed.

The injection of CO₂ into the subsurface is not a new concept. There are many projects globally, particularly in the Permian Basin of western Texas, where CO₂ injection for the purposes of enhanced oil recovery (EOR) has been underway for several decades. There has also been significant experience with underground storage of natural gas and, prior to natural gas storage, the storage of town gas (CO and H₂) in the subsurface. Large natural reservoirs of CO₂ have been exploited for several decades for commercial purposes. All such operations can provide useful insight into the engineering of CO₂ storage sites.

Additionally, there has been widespread and large scale injection of other fluids into the subsurface, especially in the oil and gas industry. For example, hydrocarbon gases are widely injected for miscible EOR, and the re-injection of oil field liquid waste, particularly oil field brines and, more recently, acid gas injection for the storage of H₂S (Hydrogen Sulphide) are common practice. In short, there is much experience globally with the safe injection of liquids into the subsurface for long-term storage.

There are also prescriptive regulations in place in many countries concerning the completion of injection wells and the abandonment procedures required when these wells are no longer needed.

As oilfield technology for EOR and waste removal has developed, so has technology to assess the nature of subsurface reservoirs and monitor the movement of the injected and native pore fluids in the reservoir. Consequently, the technologies that we now look to as techniques for monitoring the movement and potential migration/leakage of CO₂ are largely the same ones that are used for characterising the reservoir and detecting and quantifying the presence of hydrocarbons within it. Additional techniques developed in the oil and gas industry can be used to ensure safety at the surface injection facilities and to avoid overpressuring in the reservoir in underground CO₂ storage.

In some regions of the world, primarily volcanic regions, natural CO₂ leaks occur, with the CO₂ moving along natural fracture systems to the surface. Most of these seeps are benign, but in a few cases potential hazard does exist for humans and animals (e.g. Ciampino, Italy). In these instances monitoring technologies are deployed to provide early warning of potentially hazardous CO₂ accumulations. These extreme examples provide confidence that monitoring of leaks in proximity to human settlement can be effectively achieved.

Why is monitoring needed and what can it achieve?

Monitoring of CO₂ injection projects is needed for:

- health, safety and environmental purposes
- verification of the mass of CO₂ stored, for emissions trading and greenhouse gas inventory purposes
- to resolve any disputes arising from conflicts of use of the subsurface and possible contamination of underground resources

Ideally, monitoring should:

- allow the safe and stable injection of CO₂ into subsurface reservoirs
- allow the integrity of injection and monitoring wells to be assessed and monitored
- allow the location and fate of the CO₂ plume in the subsurface to be determined
- allow the project operator or regulator to assess the accuracy of performance predictions of the project
- verify that the entire mass of CO₂ that is delivered to the injection well(s) is, indeed, stored in the location that was approved for that storage
- provide early warning of migration from the intended storage reservoir or leaks to the ground surface or sea bed
- detect and measure the flux of leaks of CO₂ to the biosphere (the shallow subsurface, the ground surface, or sea bed)

Leaks or unintended migration out of the storage reservoir might in turn require mitigation activities to be undertaken. In the event that mitigation is required, the performance of the mitigation process itself will need to be evaluated.

Injection well technology:

The basics of injection well technology are straightforward. The well is drilled to the specified depth; in the case of vertical wells, this is slightly below the formation of interest. The well is then cased and the casing is cemented in place. Cementing regulations vary greatly from place to place. Cementing may be restricted to providing a seal from the ground surface to below the lowest potable water zone (the goal being to isolate and protect potable water) and at the base of the well in the formation of interest and some metres above this. However, in many cases, the casing is cemented to the surrounding rock along its entire length to ensure effective isolation of zones in the subsurface. The well is then perforated to allow access through the casing and cement into the formation of interest.

The full diameter of the well is not generally used for injection. Instead, an injection string (a smaller diameter tube) is run into the well. At the top of the formation of interest, a packer is put in place between the casing and the injection tubing to seal off the lower portion of the well. Injection then takes place. The fluid flows out of the injection tubing into the annulus between the casing and tubing and then through the casing via the perforations. The annulus, the space between the injection string and the casing itself, is sealed top and bottom. In the case of horizontal wells, there may be

casing in the formation of interest (particularly when the formation consists of unconsolidated sediments), or the hole may be uncased when the formation is sufficiently consolidated to allow the hole to remain open after drilling with no artificial support.

The surface infrastructure of the injection well is designed for safety, with valves that allow isolation of the well and automatically shut off the well in the event of an emergency. This surface infrastructure also allows monitoring equipment such as pressure gauges to be installed.

Safety requirements for injection of fluids into subsurface reservoirs

Prior to any injection into the subsurface, the fracture pressure of the reservoir rock and caprock should be determined. To avoid fracturing, with the possibility of damaging the caprock (the primary seal of the storage site), the reservoir injection pressure will usually be restricted to some level below its fracture pressure. Typically, the regulator will set limits on the surface pressure and flow rates allowable into an injector to prevent any risk of damage to the reservoir or seals.

Also, prior to any injection of fluids into the subsurface, the integrity of the well casing should be confirmed by pressure testing the well. In addition, cement bond logs should be used to determine the condition of the cement bond between the casing and the formation (this creates the seal between the outside of the well casing and the surrounding rock).

What might a monitoring program consist of?

Monitoring of CO₂ storage can conveniently be divided into stages:

- Monitoring of well bore integrity
- Measurements to determine the mass of CO₂ injected, principally derived from the fluid pressure, temperature, flow rate and gas composition at the wellhead
- Monitoring of pressure during the injection process to ensure safe and stable injection
- Monitoring of the migration and distribution of the CO₂ in the deep subsurface, focusing on the intended storage reservoir, but including any unintended migration out of the storage reservoir
- Monitoring of the shallow subsurface offshore to detect and quantify any CO₂ migrating out of the storage reservoir towards the sea bed
- Monitoring of the vadose zone onshore to detect and quantify any CO₂ migrating out of the storage reservoir towards the ground surface
- Monitoring of the ground surface and atmosphere to detect and quantify CO₂ leaking into the biosphere
- Monitoring of the biosphere to detect any subtle changes that might be related to increased CO₂ concentrations
- Monitoring of the sea bed and water column to detect and quantify CO₂ leaking to the marine environment or atmosphere
- Monitoring at the injection site to detect and quantify any leakage from surface infrastructure (for worker health and safety) and physical changes to the site (particularly heave), which may be indicative of problems below surface

- Monitoring of the wells, deep subsurface, shallow subsurface and ground surface or sea bed should continue for some period after the injection is terminated to confirm predictions of storage behaviour

Such a monitoring program would not just utilize direct and indirect measurements of CO₂ itself, but would probably also include the use of tracers to pinpoint movement ahead of any advancing CO₂ front. These tracers may also help to distinguish naturally occurring CO₂ from CO₂ leaking from the injection site.

A pre-requisite for effective monitoring is the acquisition of baseline surveys. Ideally, these should be undertaken prior to any injection of CO₂ into the storage formation, but this may not always be possible, for example when monitoring an existing EOR project. They will allow all subsequent surveys to be compared to the baseline to evaluate changes that have occurred as a result of the injection of CO₂.

Monitoring techniques:

Detailed descriptions of monitoring techniques that have been applied to, or are potentially applicable to CO₂ storage are given by Pearce et al. (2005) and Benson et al. (2004).

Monitoring well bore integrity

A wide variety of pressure sensors can be installed to measure pressure through access points in the wellhead. Fibre-optic systems are particularly useful for pressure measurement downhole as well as at surface, giving greater control on the pressures in the entire injection well system. As noted above, emergency shutdown can be triggered if pre-set threshold levels are exceeded. During well shut-in, fibre-optic temperature sensors can identify fluid exchange sites between a borehole and surrounding formations. Fibre-optic systems exist that will allow measurement along the entire wellbore in real time.

The pressure and gas composition in the annulus can be continuously monitored to determine the integrity of the injection string and the packer inside the casing used to isolate the injection zone from the remainder of the well. Changes in pressure or composition can be rapidly detected using pressure sensors or infra-red analysers and the well shut-in to determine the cause of the change. Cement bond logs can be run periodically to determine the status of the bond between the rock and the well casing. Leaks through the casing or immediately outside well bores can be detected by, for example, passive sonic monitoring.

Monitoring of the mass of CO₂ injected

The direct measurement of volumes and composition of a gas stream flowing into an injection well will allow the operator and regulator to determine the amount of gas injected with a high degree of accuracy. The measurement of produced fluids, capture of the produced CO₂, its recompression and reinjection, will allow an accurate assessment of the gross and net storage of CO₂ in an EOR project.

Monitoring equipment to determine the mass of CO₂ being injected is generally available from commercial suppliers. Typically, control systems measure gas volume, pressure and temperature at the wellhead and transmit the collected data to a control centre. Gas composition is also measured in such systems, commonly with a gas chromatograph (Wright & Majek, 1990).

Monitoring of the migration and distribution of the CO₂ in the deep subsurface

The transport and fate of CO₂ in the deep subsurface can be monitored using both direct and indirect techniques. Direct techniques measure directly the changes in the pore fluids in the subsurface, sampling either from monitoring wells or (oil or gas field) production wells. Indirect techniques include the use of a variety of remote sensing technologies which principally comprise seismic and non-seismic geophysical methods. Tracers (introduced, such as SF₆, or indigenous, such as radon) can also be used to identify fluid migration routes and breakthroughs.

Direct techniques

Fluid samples can be obtained from the injection zone by collecting samples from production wells in the case of EOR operations or from monitoring wells. Changes in fluid chemistry (pH, alkalinity, HCO₃⁻ or resistivity levels for example) can be evaluated to determine whether or not CO₂ has reached the well. Additionally, sampling and analysis of the CO₂ itself can provide an indicator of whether it is injected or naturally occurring CO₂ (for example, in the Weyburn reservoir, the stable isotopic composition of the carbon in injected CO₂ is quite different from the that of the carbon naturally present in the subsurface, so the presence of injected CO₂ at production wells can be identified by determining isotopic ratios of the carbon).

The injection of tracers has potential to more precisely determine the route and transport rate from injector to producer or monitoring well. As noted above, tracers can be artificial gases such as perfluorocarbons or noble gases, both able to be identified at very low concentrations. Noble gases, in particular, may travel through the rock more rapidly than the CO₂ providing a proxy for the route that CO₂ might take.

Direct measurement of vertical movement of CO₂ in the stratigraphic column can also be achieved in some instances with the use of observation wells or existing injection or production wells. Tools now exist that can drill through the casing and cement to collect fluid samples from behind the casing at various levels in the subsurface, and then plug the holes to prevent leakage into the well. While this technique is expensive, it may allow for periodic testing of zones of interest above the injection zone without the drilling of monitoring wells. The fluids sampled would be analysed for CO₂ and for changes to fluid chemistry resulting from increased CO₂ levels.

Well logging can be used to determine, for example, CO₂ saturation distribution in an open section of a monitoring well. Cased hole logs can also be used to detect the presence of CO₂ behind the casing, particularly if there are pre-injection logs to allow comparison. It has great potential for both detection and quantification of CO₂ in the subsurface.

Indirect techniques

The most commonly applied indirect technique is seismic technology. The use of 2-D and 3-D seismic techniques is common. Comparison of time-lapse (4-D) surveys allows migration of CO₂ in the subsurface to be followed. Examples of this technique are from Sleipner (injection into a saline aquifer) and Weyburn (injection into an oilfield). In both cases, baseline surveys were run prior to CO₂ injection so that all subsequent surveys could be compared to the pre-injection survey.

Seismic techniques can be applied in a variety of ways. The most common is 2D seismic reflection profiling or 3D seismic reflection data acquisition, where the energy source and detectors are on the surface, measuring reflection from zones in the subsurface. Other techniques include vertical seismic profiling where the source is on the surface and the detectors are placed in vertical or horizontal wells in the subsurface. Cross-well profiling can also be used where both the source and the detectors are in the subsurface. Both vertical profiling and cross-well profiling reduce the areal extent of the survey, but the level of detail may be greater. Passive techniques (micro-seismic monitoring) may also have some potential. In this case, sensors are left in place, often in wells that are scheduled for abandonment, to measure microseismic activity in the reservoir. This activity may arise from dynamic responses to changing pore pressure or reactivation of faults or fractures. The responses to these changes result in very weak seismic events in the order of 0 to -4 magnitude.

Seismic techniques are in common use and are key components of the monitoring programs in current monitoring projects such as Weyburn, Sleipner and the recently initiated In Salah project (Algeria). They are also used in pilots such as the recent tests in the Frio sandstone in Texas and at Nagaoka in Japan. They currently provide the most accurate method of detecting CO₂ in the subsurface in areas between wells. Nonetheless, surface seismic methods have limitations. They have little potential to resolve the very small impedance contrast between a reservoir rock the pores of which are filled with water containing dissolved CO₂ and one in which the pores contain water without dissolved CO₂. They also do not resolve events well below highly reflective or dispersive geological horizons such as thick evaporite deposits. Moreover, their resolution deteriorates with depth as a result of frequency attenuation.

Non-seismic geophysical techniques include the use of electrical and electromagnetic (EM), self-potential (SP) and gravity techniques. Gravity techniques, marine, ground or aerially based, can detect variations in rock or fluid density in the subsurface, for example, those caused by the injection of a lighter fluid into the pore spaces of a reservoir rock. Resolution is significantly poorer than seismic.

Electrical techniques measure natural or induced electrical or magnetic fields in the Earth. An induced electrical current will provide a measurement of the resistivity of a formation. Changes to resistivity will occur, for example, with the dissolution of minerals in the formation (decrease in resistivity) or the displacement of saline fluids by CO₂ (an increase in resistivity). The measurement of natural electrical or magnetic fields can be interpreted by comparison to a pre-injection survey to determine the presence of fluids such as CO₂ that change the characteristics of these fields. Self-potential can be measured as well, this is the ability of the earth to generate its own electrical fields. The migration of CO₂ within the rock can produce an electrical potential that is measured – this

technique may again be useful in measuring plume migration. It is a low cost but low resolution technique.

Monitoring of the shallow subsurface and marine environment to detect and quantify any CO₂ migrating into the water column or accumulating close to the sea bed

Echo-sounding and swath bathymetry may be used to detect changes in sea bed morphology that could be due to gas emerging at the sea bed, e.g. the development of pock marks. Echo-sounding can also detect bubble trains in sea water. Sparker and deep towed boomer surveys may be used to detect CO₂ in the shallow zone beneath the sea bed. Typical responses to shallow gas include acoustic blanking, reflector enhancement and bright spots. These techniques are routinely used in the oil and gas and marine surveying industries.

Monitoring of the vadose zone and ground surface to detect and quantify leakage of CO₂ to the ground surface

A number of techniques can be applied to determine the presence of CO₂ that might be released from a storage site into the vadose zone and thus to the ground surface and near-surface environment. CO₂ in near-surface environments may occur either as free gas or as CO₂ dissolved in water emerging, for example, as carbonated springs. Excellent accounts of monitoring and modeling techniques that can be applied at the ground surface and in the vadose zone are given by Oldenburg and Unger (2003) and Oldenburg, Lewicki and Hepple (2003).

Techniques applied include soil gas monitoring (Strutt et al., 2003; Klusman, 2003) and accumulation chambers placed on the ground surface (Klusman, 2003), to detect increased levels of CO₂. This can be followed up by stable carbon isotope analysis to help determine the source of any detected CO₂, and analysis for levels of the unstable isotope of carbon (¹⁴C), which may give information about the age of the carbon atoms in the carbon dioxide molecules. Marker gases such as radon that might provide clues to the location of pathways through which gases might migrate from depth may also be detected.

The major issue here is that there is a variable natural ecological (and potentially anthropogenic) background flux of CO₂ against which very small fluxes from underground need to be detected. A second issue is that such surveys sample at grid nodes and further research is needed to define the appropriate grid spacing that will provide comprehensive coverage of an area.

In groundwater, analysis of major ions (Na, K, HCO₃⁻ etc.), alkalinity and pH, as well as searching for hydrocarbon gas and the ratio of stable carbon isotopes can determine changes to CO₂ quantity and source. In addition, contamination by trace elements such as lead and arsenic, which may be mobilized by changing water pH, may be indicators of increased CO₂ levels. As in soil gas analysis or gas analysis from accumulation chambers, isotopic analysis of the CO₂ will help to determine its source, in particular shallow biogenic sources of CO₂ will have a different isotopic composition to CO₂ from fossil sources. Artificial tracers injected with the CO₂ such as perfluorocarbons or noble gases, detectable at very low concentrations, may provide an indication of the potential for leakage from the storage zone.

Techniques such as hyperspectral imagery from airborne surveys can indicate changes to vegetation productivity that could be the result of changing conditions in the vadose zone (Pickles & Cover 2005). Due to the density difference between gaseous CO₂ and the atmosphere, the CO₂ will tend to accumulate in the vadose zone, even with low flux levels, and at high levels (for example Mammoth Mountain) can negatively impact plant growth even to the point of killing the plants. Such biosphere responses are clear signals of ecosystem disturbance, drawing attention to the need for more detailed examination. Some plant responses to chronic raised atmospheric levels of CO₂, such as reduced stomatal density, could provide a low-tech way of identifying leakage and have been observed around natural seeps. Tree kills and other vegetational changes are routinely used in the identification of methane leaks from buried gas pipelines.

Measuring a change in flux of CO₂ into the atmosphere can be undertaken with a variety of infra-red techniques (Schuler & Tang, 2005). Two techniques that have been used to date are accumulation chambers (Klusman, 2003) and eddy covariance (Miles, Davis and Wyngaard, in press).

Various remote infra-red techniques may be used to try to analyse for increasing CO₂ concentrations in the near surface zone of the atmosphere using airborne or even satellite based systems. In any of these techniques, the increasing flux of CO₂ would need to be very high for the analytic techniques to pick up variance. The more remote the sensor, the less likely it is to be able to pick up changing levels of CO₂. For example, the averaging effect of airborne or satellite based measurements of CO₂ through a long column of atmosphere will effectively mask most leaks of CO₂.

Monitoring ground surface movement:

Accurate tiltmeters, or satellite imagery can be used to measure heave of the ground surface or injection wellhead. This may be indicative of potential problems in the subsurface. However, this is not always the case, and under favourable circumstances, satellite-based ground elevation measurement techniques have the potential to help to identify plume migration in the subsurface.

Monitoring of air quality to ensure worker health and safety

For worker health and safety, particularly if there are contaminants in the CO₂ stream such as H₂S (for example, acid gas injection sites in Alberta), there will be monitoring equipment sited at and around the surface facilities to directly measure any leakage. Infra-red gas detectors are commonly used to determine the levels of CO₂ in the ambient air surrounding the wellhead.

Gaps discussion:

The above discussion covers most of the techniques either currently being used or proposed to monitor:

- The injection of CO₂ into the subsurface
- The condition of wells and their bond to the surrounding rock
- The migration and distribution of injected CO₂ within the intended storage reservoir

- Its migration out of the intended storage reservoir and subsequent distribution
- Its potential transport to the near surface, ground surface or sea bed
- Its flux through the ground surface or sea bed, into the atmosphere or sea

These techniques vary greatly in resolution and cost. The necessary precision of measurement does not exist in all monitoring spheres and there is also a need to identify the least-cost solutions able to meet the necessary monitoring requirements.

There are no major perceived gaps in our ability to monitor the mass of CO₂ or other gases injected into the subsurface. This is common practice in enhanced oil recovery projects.

There are no major perceived gaps in our ability to monitor CO₂ escapes from surface facilities at injection sites for health and safety reasons. This is also common practice in enhanced oil recovery projects.

There are no major perceived technology gaps in monitoring the condition of new wells and their bond to the surrounding rock. The ability to assess the condition of pre-existing abandoned wells beyond empirical observation of leaks (i.e. to determine whether they are likely to leak in the future) is, however, a major technology gap.

Shallow subsurface monitoring of CO₂ is also a mature technology in terrestrial settings, the main gaps being those of frequency and spacing, and strategies required in different terrestrial climate regimes (e.g. deserts, temperate grassland, tundra, etc.). In subaqueous settings, it is less clear how much CO₂ measuring devices used by marine biologists (often for mesocolumn and shallower applications) can be adapted for benthonic settings, particularly within shallow sediments. Very little is also known about the possibility of using ecosystem changes, or indicator species, as monitoring signals for CO₂ seepage into the hydrosphere. Such techniques are used to monitor pollution effects, such as nitrification from agricultural and sewage disposal activities.

A range of tools are available for monitoring the migration and distribution of injected CO₂ within the storage reservoir and its potential migration out of the storage reservoir and subsequent distribution. However, these are at best semi-quantitative and their performance will be highly site-specific and dependent on the local geology. In general, detection of CO₂ in the subsurface is better than quantification. Seismic reflection surveying is commonly a good method of detecting free gas phase or supercritical CO₂, but it may be of limited effectiveness beneath, for example, thick salt horizons. Also, it will not detect dissolved CO₂. Well logging and direct sampling can provide a better understanding of CO₂ saturation distribution in the reservoir and certain tools may be able to detect dissolved CO₂ from changes in resistivity, pH or direct sampling. In general, there is a major gap in our ability to independently and accurately verify the mass of CO₂ stored in a subsurface reservoir.

Tools are available to detect CO₂ in the vadose zone onshore and in the shallow subsurface offshore. However, there is a technology gap in quantification of the mass of CO₂ present in shallow accumulations in offshore areas.

Tools and methodologies are available for detecting and monitoring CO₂ fluxes from the vadose zone to the atmosphere. These require further field trials to identify best practice. There is room for technology research and development in this field.

Technologies exist that can detect bubble trains in seawater. These provide a means of detecting CO₂ fluxes through the sea bed. However, they will not detect dissolved CO₂ and some cost-effective means of direct detection in the marine environment such as sea water sampling needs to be developed.

The real gaps in the technology for monitoring fall into the areas of cost and level of accuracy. While there is some discussion around the ability to quantify results, the key is the accuracy and repeatability of results.

From another perspective, if it can be shown that there is little or no leakage from the subsurface container, the ability to quantify the amount of CO₂ in the reservoir or saline aquifer based on remote sensing techniques is largely irrelevant, the inflow metering will be quite adequate. The discussion resides, therefore around several other factors:

- The ability to identify leaks in the subsurface.
- The ability to determine the risk of leakage along wellbores.
- The ability to identify faults or fractures that may be encountered by the expanding CO₂ plume that may be open or could be opened to provide a conduit out of the subsurface storage container.
- The ability to identify surface or near-surface leaks of CO₂.
- The ability to define what thresholds and types of leakage are acceptable/unacceptable with respect to the different requirements of carbon trading, health and safety and environmental protection. These thresholds have to be measurable/quantifiable by appropriate monitoring technologies and strategies

These issues and the gaps will be discussed below:

Leaks in the subsurface: The current work on storage projects is providing increasing confidence that seismic interpretation is sufficiently accurate that some leaks may be identified before large volumes of CO₂ can escape. Work at Lawrence Berkeley National Laboratories suggests that volumes as small as 10,000 tonnes of CO₂ could be consistently resolved in the subsurface. In the instance of Weyburn, this volume may be as low as 2,500 tonnes. The work at Sleipner suggests that zones as thin as 1 metre vertically with high concentrations of CO₂ can be resolved in the subsurface. This generally assumes that the CO₂ spreads out in an overlying aquifer, vertical or sub-vertical migration of CO₂ along a fault or fracture may be more difficult to identify.

Some of the current work suggests some quantifiability of the results from the seismic surveys. As noted above, the key question is the identification of leaks rather than assessing the volume stored. There is also a question of leak identification in the absence of a baseline survey, for example in the EOR projects of West Texas where no baseline surveys were undertaken. The other element of the seismic survey is the cost of undertaking repeat surveys. While seismic surveys are expensive,

they represent only a small proportion of a total storage project cost. There is still, however, a need to continue to bring down the cost of surveys and the ensuing data processing.

It is currently not possible to use the non-seismic geophysical techniques to identify leaks in the subsurface, unless they are very large, probably several orders of magnitude larger than might be seen by seismic techniques. The use of observation wells with permanent or periodic sampling points in horizons overlying the injection zone would be able to identify leaks in the area close to the well by means of geochemical monitoring or direct recognition of CO₂ in the zone of interest. There has been no evaluation of permanent or semi-permanent sampling points in an observation well to determine leakage into overlying zones.

Leakage along the wellbore: One of the gaps remaining is a better understanding of wellbore integrity over the long-term, including the steel of the casing and any physical or chemical changes to the cement. There is a need to better understand the interpretation of cement bond logs to determine what these logs are indicating about the quality of the cement and bonding outside the casing. Effective log interpretation may result in the provision of an indication of potential problem areas or identify degradation and leakage along the wellbore following injection of CO₂ into a storage zone. It is likely that some invasive testing will be required as well as laboratory work to provide verification of the log interpretation.

Measurement at the surface of CO₂ in the vadose zone or leaking across the soil-atmosphere interface should be relatively straightforward using soil gas surveys and infra-red analysis.

Identification of faults and fractures: One of the keys for assessing the risk of storage, particularly in saline aquifers where the amount of drilling will be small and the knowledge of the reservoir consequently fairly limited will be the understanding of the nature of the fracture system. The use seismic, perhaps in association with gravity surveys, may provide the answer regarding identification of open fractures that might be intersected by an expanding CO₂ plume. To maximize the rate of dissolution of CO₂ in reservoir fluids, particularly in saline aquifers, the faster and further the CO₂ plume expands the better. In other words, the more rapidly the CO₂ encounters unsaturated water the quicker it will dissolve and remove the buoyancy effect. This has the negative effect in terms of risk in the sense that the “slippery” CO₂ plume (*sensu* Benson et. al, 2004) will migrate further and this increases the chance of encountering fractures that may be conduits to surface. Careful geochemical analysis and geological interpretation prior to use of the site may help alleviate this concern by identifying geochemically separate fluids in the injection zone and overlying zones, which would suggest hydrodynamic isolation for extended periods.

The use of cheaper, but lower resolution techniques to follow the plume may be adequate to identify plume migration. These techniques will not, however, allow identification of potentially problematic fractures.

Surface and near-surface leaks: Direct sampling of gases in the vadose zone for appropriate isotopically distinct carbon or for precursor or indicator gases is undoubtedly the most effective way. In the freshwater zone, changes to geochemistry in the water, perhaps with mobilization of some heavy metals, is also indicative of increased flux of CO₂ from below. Remote sensing of CO₂ flux across the geosphere-atmosphere interface is a lot more problematic and will require some additional

work to develop techniques that can measure low flux increases. Analysis of vegetational changes by hyperspectral surveys could show changes to gas levels in the vadose zone quite effectively, but more work will be required to determine optimal times for surveys in different climatic zones, a better understanding of the influence of soil type etc.

Needs analysis:

- Reduced cost to seismic surveys and the interpretation of the data.
- Improved vertical resolution of seismic surveys
- Improved quantification of seismic results as a means of determining leaks in the subsurface
- Improvements in the resolution of non-seismic geophysical techniques
- Improved recognition and interpretation of the nature of faults and fractures with seismic, non-seismic or the combination of techniques
- Improved remote sensing to allow identification of increased CO₂ fluxes at surface that might be from deeper sources
- Development of improved wellbore monitoring techniques to allow interpretation of activity outside the casing, but in the immediate wellbore area.
- Development of guidelines to assist in the determination of effective pre-injection surveys, particularly in saline aquifer examples. In particular to help in the determination of hydrodynamic isolation of the proposed injection zone
- Improved interpretation of cased hole logs to determine potential activity outside the casing or identification of problems with cement bonding
- Improved integration of monitoring techniques and the results of the application of these techniques
- Improved methods for detecting CO₂ seeps into subaqueous settings, particularly dissolved CO₂
- Identify thresholds of leakage that can be measured and the implications of these on formulating regulation of sites

Conclusions and recommendations:

In conclusion, there are a wide variety of techniques available to examine all phase of CO₂ injection into the subsurface and to monitor its fate and transport in the subsurface. The more direct the technique, the more certain the results in terms of the level of confidence placed on the outcomes. The ability to use direct techniques is limited by the cost, for example, the drilling of observation wells for direct sampling and the risk imposed by drilling these holes for becoming leakage pathways will limit their application. Direct techniques also have some limitations in terms of the areal extent of the information gained through direct observation.

Remote interpretation techniques to determine what is happening in the subsurface to the CO₂ currently have resolution issues. Seismic techniques are the best suited, but still have some limitations regarding resolution, cost and quantification. Non-seismic geophysical techniques show some promise, but require more work to improve resolution. There is likely to be some improvements in the integration of results from these various techniques to improve overall effectiveness of interpretation. Remote sensing of CO₂ fluxes from the surface may never be effective, but some additional work in this area could be undertaken. The most promising is the use

of hyperspectral imagery to identify changes to vegetation that might be related back to CO₂ induced changes to plant growth as the level of CO₂ in the vadose zone changes.

Ultimately, it will be the level of risk associated with a given site that will determine the amount and type of monitoring that is undertaken. In what might be considered as safe sites, based on effective pre-injection surveys of the geology, the nature of the caprock etc., the need to improve monitoring techniques might well be minimal. In areas with a higher real or perceived risk, the need to establish a more complex monitoring program may well require ongoing improvements to the resolution of the techniques under examination. The nature of the techniques will also change depending on the level of knowledge available for the site, for example, oil fields may use slightly different techniques than saline aquifers where there is less information available at the start of operations.

In short, further work is required. This should be a continued research effort to improve the interpretation of the variety of remote sensing techniques being employed. While not all avenues will be required, it is not clear that any techniques should be abandoned at this point. The work to improve monitoring techniques should progress with risk assessment work – the level of risk acceptable to the public and regulator will determine the requirements of the monitoring program (level of accuracy, length of time monitoring must continue etc.). Ideally, there will be more integration of research effort and the use of sites with extensive geological knowledge to provide the best chances for success in improvement of techniques in these early stages. Activities such as the IEA Greenhouse Gas R&D Programme networks on monitoring and verification, risk assessment and wellbore integrity will be important to overall success of this effort and should be encouraged. Better integration of major projects should also be encouraged to optimize results in these early stages.

Well logging has great potential for monitoring many aspects of CO₂ storage in the subsurface. It is recommended that submissions be invited from well logging companies on the functionality and resolution of available logging tools that might have relevance to the monitoring of CO₂ storage sites.

Some useful references:

- Arts, R., Eiken, O., Chadwick, R.A., Zweigel, P., van der Meer, L.G.H. & Zinszner, B. 2003. Monitoring of CO₂ Injected at Sleipner Using Time-Lapse Seismic Data. In: J. Gale & Y. Kaya (Eds.) *Greenhouse Gas Control Technologies*, Volume 1, 347-352, Pergamon, Amsterdam.
- Benson, S.M., E. Gasperikova and G.M. Hoversten, 2004. Overview of monitoring techniques and protocols for geological storage projects. IEA Greenhouse Gas R&D Programme report.
- Gunter, W. D., Bachu, S., and Benson, S. M., 2003. "The Role of Hydrogeological and Geochemical Trapping in Sedimentary Basins for Secure Geologic Storage of Carbon Dioxide," in *Geological Storage of Carbon Dioxide for Emission Reduction Technology*, S. J. Baines, J. Gale and R.H. Worden (eds).
- Gunter, W.D., Chalaturnyk, R.J. and Scott, J.D., 1998, Monitoring of Aquifer Disposal of CO₂: experience from underground gas storage and enhanced oil Recovery. Proceedings, GHGT-4, Interlaken, Switzerland, pp. 151-156.

- Klusman, R.W., 2003. Rate measurements and detection of gas microseepage to the atmosphere from an enhanced oil recovery/sequestration project, Rangely, Colorado, USA. *Applied Geochemistry*, 18, 1825-1838.
- Miles, N.L., Davis, K.J. & Wyngaard, J.C. in press. Using eddy covariance to detect leaks from CO₂ sequestered in deep aquifers. Proceedings of the 7th International Conference on Greenhouse Gas Control Technologies, Vol.2.
- Oldenburg, C.M., Lewicki, J.L. & Hepple, R.C. 2003. *Near Surface Monitoring Strategies for Geologic Carbon Dioxide Storage Verification*. Earth Sciences Division, Ernest Orlando Lawrence Berkeley National Laboratory, Berkeley, CA 94720, USA, 54pp.
- Oldenburg, C.M. & Unger, J.A. 2003. On Leakage and seepage from Geologic Carbon Sequestration Sites: Unsaturated Zone Attenuation. *Vadose Zone Journal* 2:287-296.
- Pearce, J.M., Chadwick, R.A., Bentham, M.S., Holloway, S. & Kirby, G.A. in press 2005. A Technology Status Review of Monitoring Technologies for CO₂ Storage. DTI Cleaner Coal Fossil Fuels Programme Report No. CoalR, DTI Pub URN 05/
- Pickles, W.L. & Cover, W.A. 2004. Hyperspectral Geobotanical Remote sensing for CO₂ Storage Monitoring. In: Thomas D.C. & Benson, S.M. (Eds) *The CO₂ Capture and Storage Project (CCP)*, Volume II, Elsevier Science Ltd.
- Schroot, B.M. & R.T.E. Schüttenhelm, 2003. Shallow gas and gas seepage: expressions on seismic and other acoustic data from the Netherlands North Sea. *Journal of Geochemical Exploration*, 4061, 1-5.
- Schuler, P. & Tang, Y., 2005. Atmospheric CO₂ Monitoring Systems. In: Thomas D.C. & Benson, S.M. (Eds) *The CO₂ Capture and Storage Project (CCP)*, Volume II, Elsevier Science Ltd.
- Strutt, M. H., Beaubien, S. E., Baubron, J.-C., Brach, M., Cardellini, C., Granieri, R., Jones, D. G., Lombardi, S., Penner, L., Quattrocchi, F. and Voltatoni, N. (2003). Soil gas as a monitoring tool of deep geological sequestration of carbon dioxide: preliminary results from the EnCana EOR operation in Weyburn, Saskatchewan (Canada). In: Gale, J. and Kaya, Y. (eds) *Greenhouse Gas Control Technologies, Volume I*. Elsevier Science Limited, Oxford, pp. 391-396.
- Wilson, M. and M. Monea (eds), 2004, IEA GHG Weyburn CO₂ Monitoring and Storage Project, Report 2000-2004. Proceedings of the 7th International Conference on Greenhouse Gas Control Technologies, Vol.3.